



**Integrated Control Systems
International™**

**BARCODE MACHINE READABLE
ELECTRONIC EXIT VERIFIER
MASI® Model MXV-1200**



Model MXV-1200 Exit Verifier

FEATURES:

- *Easy side access ticket retrieval.*
- *Non-contact thermal print technology*
- *24VDC low voltage operation*
- *Internal Batteries allow for operation during power interruptions*
- **Print On The Fly** Barcode AutoRead
- *Rugged rust-resistant zinc plated steel construction.*
- *Built-In thermostatically controlled heaters.*
- *Large back-lit LCD displays Date & Time, and optional programmable message.*
- *Optional built-in intercom*
- *On-Line or Off-Line Operation capable*
- *Tickets 4 or 7 mil thick, 4" by 2"*
- *Optional Card Reader mounted on face of Exit Verifier.*



Easy Accessibility!

icsi

917 Eldorado Drive
Escondido, CA 92025-6717

Phone: 760 - 432 - 8337
Fax: 760 - 432 - 8347
Website: www.icsiparc.com



I. Purpose:

The Model MXV-1200 Exit Verifier is a revenue control device that provides a "vend" signal when a ticket is issued. This "vend" signal causes a lift-arm barrier gate to activate, and allow access into the facility.

II. Features & Functions:

- A. The Model MXV-1200 Barcode Exit Verifier is designed to issue a printed date & time, barcode machine-readable ticket to an entering parking patron.
- B. The MXV-1200 is activated by a push-button, loop detector, treadle, or other triggering device.
- C. The Exit Verifier accepts one ticket from each exiting parking patron.
- D. Each ticket may be fully preprinted with general facility location and contract disclaimer data.
- E. The Exit Verifier may be equipped with an access control reader for Monthly Cardholders, and/or a highly recommended remote intercom station.

III. Physical Description:

- A. The Exit Verifier's overall dimensions are 15" wide, by 15" deep, by 40" in height. It weighs 150 pounds without ticket roll.
- B. The electrical power requirements for the Exit Verifier are 115VAC at 60Hz, or 220VAC at 50Hz. An internal UL approved step-down transformer converts this current into the 24VDC required to power all of the electrical circuitry within the device.
- C. Each Exit Verifier is equipped with an internal back-up battery to provide continued service even in the event of a general power outage.
- D. The Exit Verifier contains a microprocessor-controlled circuit that includes a date/time clock calendar. This microprocessor may be programmed with its operating parameters remotely via available RS-232 communications connection.
- E. The Exit Verifier is constructed of heavy duty rolled steel, which is zinc plated for rust inhibition, and then powder coated with sealing rust resistant paint. The standard color is white or yellow, but the device may be ordered with special paint colors.

